

**Amendment to the Claims:**

1. (Previously presented) A gradient coil for a magnetic resonance imaging apparatus, the gradient coil including:
  - a fingerprint-patterned primary coil defining an inner cylindrical surface;
  - a shield coil defining an outer cylindrical surface coaxially aligned with the
  - 5 inner cylindrical surface and having a larger cylindrical radius than the inner cylindrical surface; and
  - a plurality of coil jumps electrically connecting the primary and shield coils, the coil jumps defining a non-planar current-sharing surface extending between an inner contour coinciding with the inner cylindrical surface and an outer contour coinciding
  - 10 with the outer cylindrical surface;
  - the primary coil, shield coil, and coil jumps cooperatively defining a current path that passes across the current-sharing surface between the inner and outer contours a plurality of times.
2. (Previously presented) The gradient coil as set forth in claim 1, wherein:
  - the primary coil extends axially a primary coil length along the inner cylindrical surface; and
  - the shield coil extends axially a shield coil length along the outer cylindrical
  - 5 surface;
  - the shield coil length not equal to the primary coil length.
3. (Previously presented) The gradient coil as set forth in claim 2, wherein:
  - the current sharing surface corresponds to a curved surface of a frustum of a cone with a cone angle defined by a difference between radii of the inner and outer cylindrical surfaces and a difference between the primary and shield coil lengths.
4. (Previously presented) The gradient coil as set forth in claim 1, wherein:
  - the shield coil is fingerprint patterned.

5. (Withdrawn) A gradient coil comprising:

a primary coil defining an inner cylindrical surface;

a shield coil defining an outer cylindrical surface coaxially aligned with the inner cylindrical surface and having a larger cylindrical radius than the inner  
5 cylindrical surface; and

a plurality of coil jumps electrically connecting the primary and shield coils, the coil jumps defining a non-planar current-sharing surface extending between an inner contour coinciding with the inner cylindrical surface and an outer contour coinciding with the outer cylindrical surface, the primary coil, shield coil, and coil jumps  
10 cooperatively defining a current path that passes across the current-sharing surface between the inner and outer contours a plurality of times, wherein the primary coil includes communicating primary coil turns that electrically connect with a coil jump and isolated primary coil turns that do not electrically connect with a coil jump.

6. (Withdrawn) The gradient coil as set forth in claim 5, wherein the shield coil includes:

communicating shield coil turns that electrically communicate with communicating primary coil turns via connecting coil jumps.

7. (Withdrawn) The gradient coil as set forth in claim 5, wherein at least some of the isolated primary coil turns are electrically interconnected to define an isolated primary sub-coil, and the gradient coil further includes:

5 a switch having at least:

a first state in which the isolated primary sub-coil is electrically connected with the communicating primary coil turns, and

a second state in which the isolated primary sub-coil is electrically isolated from the communicating primary coil turns;

10 the first and second states corresponding to first and second selectable fields of view.

8. (Withdrawn) The gradient coil as set forth in claim 7, wherein the isolated primary sub-coil is deenergized in the second state.

9. (Withdrawn) The gradient coil as set forth in claim 7, wherein the isolated primary sub-coil is energized with opposite polarities in the two states.

10. (Withdrawn) The gradient coil as set forth in claim 7, wherein the gradient coil further includes:

a second shield coil that is energized in one of the two states to improve uniformity of the corresponding field of view.

11. (Withdrawn) The gradient coil as set forth in claim 5, wherein at least some isolated primary coil turns are interconnected to define a selectively electrically switched primary sub-coil, the gradient coil further including:

5 a second shield coil that is selectively energized in conjunction with switching of the primary sub-coil to define a variable field of view.

12. (Original) The gradient coil as set forth in claim 1, further including:

a shielded correction coil that cooperatively adjusts a field of view over a continuous range.

13. (Previously presented) The gradient coil as set forth in claim 1, further including:

5 a generally cylindrical cold shield coaxially aligned with the outer cylindrical surface and having a larger cylindrical radius than the outer cylindrical surface, the cold shield carrying eddy current that produces a substantially spatially constant residual eddy current effect.

14. (Original) The gradient coil as set forth in claim 13, wherein the substantially spatially constant residual eddy current effect is non-zero.

15. (Original) The gradient coil as set forth in claim 1, wherein the gradient coil is a transverse gradient coil.

16. (Previously presented) The gradient coil as set forth in claim 1, wherein the coil jumps are selected to minimize the stored energy of the coil.

17. (Original) A magnetic resonance scanner comprising:  
a main magnet for generating a temporally constant magnetic field;  
a gradient coil as set forth in claim 1 for inducing magnetic field gradients  
5 across the temporally constant magnetic field;  
at least one RF coil disposed adjacent the gradient coil;  
an RF transmitter connected with one of the RF coils for inducing and  
manipulating resonance;  
an RF receiver connected with one of the RF coils for demodulating induced  
10 resonance; and  
a reconstruction processor for reconstructing the demodulated resonance into an  
image representation.

18. (Canceled)

19. (Withdrawn) A method for producing a magnetic field gradient in a magnet  
bore of a magnetic resonance imaging apparatus, the method including:  
selecting a total number of coil jumps which minimizes the stored energy of the  
5 gradient coil;  
circulating an electrical current through a primary coil that defines an inner  
cylindrical surface;  
circulating the electrical current through a shield coil that defines an outer  
cylindrical surface coaxially aligned with the inner cylindrical surface and having a  
10 larger cylindrical radius than the inner cylindrical surface; and  
communicating the electrical current back and forth between the primary and  
shield coils via the selected number of non-planar coil jumps a plurality of times.

20. (Withdrawn) The method as set forth in claim 19, wherein the selecting of a  
total number of coil jumps includes:  
constraining selection of the coil jumps to produce substantially spatially  
constant residual eddy current effect from a cold shield that surrounds the shield coil.

**21.** (Withdrawn) The method as set forth in claim **19**, further including:

computing current densities on the inner and outer cylindrical surfaces using constraints including minimizing stored energy and minimizing the variation of the residual eddy current effect, the current densities being generally non-zero at the inner  
5 and outer contours;

arranging coil turns of the primary and shield coils to approximate the computed current densities on the inner and outer cylindrical surfaces; and

during the arranging of coil turns, arranging coil jumps to approximate the computed non-zero current densities at the inner and outer contours.

**22.** (Withdrawn) The method as set forth in claim **21**, further including:

simultaneously with the computing of current densities on the inner and outer cylindrical surfaces, computing current densities on a current-sharing surface, the arranging of coil jumps being further constrained to approximate the computed  
5 current densities on the current-sharing surface.

**23.** (Withdrawn) The method as set forth in claim **21**, wherein the computing of current densities further includes:

constraining the current densities to produce a substantially spatially constant eddy current effect produced by a current density in a cold shield that surrounds the  
5 shield coil.

**24.** (Withdrawn) The method as set forth in claim **23**, further including:

applying a gradient pre-emphasis that substantially cancels a magnetic field produced by the eddy currents in the cold shield.

**25.** (Withdrawn) A method for producing a magnetic field gradient in a magnet bore of a magnetic resonance imaging apparatus, the method including:

circulating an electrical current through a primary coil that defines an inner cylindrical surface, the primary coil including a plurality of coil loops;

- 5           circulating the electrical current through a shield coil that defines an outer  
cylindrical surface coaxially aligned with the inner cylindrical surface and having a  
larger cylindrical radius than the inner cylindrical surface;  
          communicating the electrical current back and forth between the primary and  
shield coils via a plurality of non-planar coil jumps a plurality of times; and  
10          selectively electrically isolating at least some primary coil loops from the  
communicating of the electrical current between the primary and shield coils via the  
plurality of coil jumps, the selective electrical isolating defining a coil set which  
combined with a second shield coil provides a second selectable field of view.

26. (Withdrawn) The method as set forth in claim 19, wherein the primary coil  
includes a plurality of coil loops, the method further including:

- selectively removing at least some primary coil loops from the communicating  
of the electrical current between the primary and shield coils via the plurality of coil  
5          jumps, the selectively removed primary coil loops being interconnected to define a  
primary sub-coil; and  
          circulating second electrical current through the primary sub-coil and a second  
shield coil the electrical current and the second electrical current cooperating to  
produce a gradient coil field of view that is different from a gradient coil field of view  
10       produced without the selective removing and circulating of second electrical current.

27-28.       (Canceled)

29. (Withdrawn) The method as set forth in claim 19, further including:

- arranging the coil jumps such that the primary coil includes at least one  
communicating primary coil turn that electrically connects with a coil jump and at  
least one isolated primary coil turn that does not electrically connect with a coil jump.